



Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Reflector Trim	Frame-In Kit — See Individual Frame-In Kit Specification Sheets			
2090	Line Voltage			
	Frame-In Kit	Installation Type	Lamping	Height
	2000P1	Standard Non-IC	50W PAR20	5 1/4"
	2002P1	Standard Non-IC		5 3/16"
	2003R	Non-IC Remodeler		5 3/16"
	2000IC	IC	50W PAR20	5 1/4"
	2000AIC	IC AirSeal®		5 1/4"

Features

- Housing:** Hydroformed aluminum, .040 thk. min. Non-yellowing, gloss white powder coat finish for permanent reflectivity and surface protection.
- Trim Flange:** Frosted clear polycarbonate flange ring. Pull down and release for toolless relamping.
- Frame-In Kit:** (2002P2 standard frame shown) Other frames shown below. See Frame-In Kit specification sheets for more details.
- Glass:** Processed borosilicate glass textured diffuser. Smooth surface on exposed side for wipe down cleaning. Meets NEC® requirements for spas and hot tubs. May be installed less than 7' 6" above max water surface height.

Labels

UL (Suitable for Wet Locations - Covered Ceilings only), I.B.E.W.
NEC® is a registered trademark of the National Fire Protection Association.
US Patent Numbers: 5,045,985

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
www.lightolier.com © 2008 Philips Group • G0708